

P8

faster, smaller, quieter printing



P8 features:

- Bi-directional printing improves print speeds
- Quiet operation
- Easy-to-load pre-printed or plain roll paper
- Paper Out and Power indicator lights
- Compatible with all Hypercom T7 terminals



innovation. results. leadership.



www.hypercom.com

P8

faster, smaller, quieter printing

High Performance

The Hypercom® P8 family of printers offer higher performance, greater reliability and lower operating costs, making them superior to any other printer on the market.

Print Choice

The P8 printers are available in either 40-column friction feed (P8F) or 23-column sprocket feed (P8S) models, making them a sensible choice for printing credit card vouchers.

The P8F roll printer helps speed transaction times with rapid paper advance at the rate of 13 lines per second.

The P8S sprocket feed printer provides printing on pre-printed forms. These forms are particularly suitable for custom applications that require printing of large amounts of standard text or complex international character sets. With paper advanced at a rapid 16 lines per second, customers are not kept waiting. Paper loading is simple and easy with both Hypercom printers.

In addition, both P8 printers provide quality receipts in a new, compact, quiet design. P8 printers are powered by the terminal, eliminating the need for separate power supplies and outlets.

Specifications:

Printer Type

P8F: Friction feed with 40 columns
P8S: Sprocket feed with 23 columns

Paper

1, 2, or 3-ply carbonless

P8F: 3 in - 3.35 in/76 mm - 85 mm

P8S: 3 in/76 mm

Font

Bi-directional, 4 lines per second

P8F: 7x7 impact dot matrix

P8S: 5x7 impact dot matrix

Feed Speed

P8F: 13 lines per second

P8S: 16 lines per second

Character Size (w/h)

P8F: 1.59 x 2.87 mm

P8S: 1.97 x 2.87 mm

Other Printer Features

Line spacing: 1/6 in

Ribbon size: 13 mm

Power

24 Vdc, 1A supplied by terminal

Footprint

P8F: 5.5 in x 9.0 in x 4.25 in/13.97 cm x 22.86 cm x 10.70 cm

P8S: 5.5 in x 8.0 in x 5.0 in/13.97 cm x 20.32 cm x 12.7 cm

Weight

2.25 lbs/0.84 kg

Environment

Temperature: 0-45 C/32-115 F

ESD: 12,000 volts

Reliability

2,000,000 lines (MTBF calculated)

Head life: 50,000,000 characters

Ribbon life (black): 1,200,000 characters

Specifications subject to change without notice.

World Headquarters/ North America

Hypercom Corporation
2851 W. Kathleen Road
Phoenix, Arizona 85053
USA
Tel: +1.602.504.5000
Fax: +1.602.866.5380

Latin America

Hypercom Indústria e Comercio LTDA
Centro Empresarial Atibaia
Rodovia Dom Pedro I, KM 87, 5
Av. Tegula, 888-Ponte Alta
Atibaia 12940-000, Brazil
Tel: +55.11.4417.7000
Fax: +55.11.4417.7060

Asia/Pacific Rim

Hypercom Asia Ltd.

21/F Metro Centre II
21 Lam Hing Street
Kowloon Bay, Kowloon
Hong Kong
Tel: +85.2.2561.6800
Fax: +85.2.2561.5890

Europe/Middle East/Africa

Hypercom EMEA, Inc.

Unit 2, Woking Eight
Forsyth Road
Woking, GU21 5SB,
United Kingdom
Tel: +44.1483.718600
Fax: +44.1483.718601

©2001-2004 Hypercom Corporation, all rights reserved. Hypercom and the Hypercom logo are registered trademarks of Hypercom Corporation. All other products or services mentioned in this document are trademarks, service marks, registered trademarks or registered service marks of their respective owners.

Celebrating 26 years of technology excellence, innovation and leadership, Hypercom Corporation is a leading global provider of electronic payment solution that add value at the point-of-transaction for consumers, merchants and acquirers, and yield increased profitability for its customers.

Widely recognized as the global payment technology innovator, Hypercom delivers comprehensive card payment terminal, network and server solutions that help merchants and financial institutions generate revenues and increase profits.

Headquartered in Phoenix, Arizona, Hypercom's card payment terminal, network and server solutions are leading the transformation of electronic payments in more than 100 countries.

innovation. results. leadership.



www.hypercom.com